

OUTRIGGER RAM GROUND PRESSURE							
CRANE	CRANE NEW	Max REACTION		Foot pad diameter		Ground presure	
MICRO_M10A	MICRO_M10A	daN	1681	mm	180	daN/cm ²	6.6
		lbf	3779	inch	7.087	psi	95.81
MICRO_M15A	MICRO_M15A	daN	2391	mm	180	daN/cm ²	9.4
		lbf	5375	inch	7.087	psi	136.28
MICRO_M20A	MICRO_M20A	daN	2401	mm	180	daN/cm ²	9.4
		lbf	5398	inch	7.087	psi	136.85
MICRO_M25A	MICRO_M25A	daN	2758	mm	180	daN/cm ²	10.8
		lbf	6200	inch	7.087	psi	157.20
MICRO_M30A	MICRO_M30A	daN	3195	mm	180	daN/cm ²	12.6
		lbf	7183	inch	7.087	psi	182.10
	M40A.1	daN	3166	mm	180	daN/cm ²	12.4
		lbf	7117	inch	7.087	psi	180.45
F20		daN	2070	mm	140	daN/cm ²	13.4
		lbf	4654	inch	5.512	psi	195.03
F22A	F22A.0	daN	2365	mm	180	daN/cm ²	9.3
		lbf	5317	inch	7.087	psi	134.80
F28A		daN	2915	mm	140	daN/cm ²	18.9
		lbf	6553	inch	5.512	psi	274.65
	F26AFS.0	daN	2487	mm	120	daN/cm ²	22.0
		lbf	5591	inch	4.724	psi	318.94
	F26A.0	daN	2487	mm	180	daN/cm ²	9.8
		lbf	5591	inch	7.087	psi	141.75
F28B	F28A.0	daN	2916	mm	180	daN/cm ²	11.5
		lbf	6555	inch	7.087	psi	166.20
F30A		daN	2803	mm	140	daN/cm ²	18.2
		lbf	6301	inch	5.512	psi	264.09
F30CY	F30CY.0	daN	2238	mm	180	daN/cm ²	8.8
		lbf	5031	inch	7.087	psi	127.56
	F30M.0	daN	2238	mm	120	daN/cm ²	19.8
		lbf	5031	inch	4.724	psi	287.00
	F32A.0	daN	2932	mm	180	daN/cm ²	11.5
		lbf	6591	inch	7.087	psi	167.11
F38A	F38A.0	daN	3364	mm	180	daN/cm ²	13.2
		lbf	7563	inch	7.087	psi	191.73
F40A		daN	3603	mm	140	daN/cm ²	23.4
		lbf	8100	inch	5.512	psi	339.47
F40B	F40A.0	daN	3614	mm	180	daN/cm ²	14.2
		lbf	8125	inch	7.087	psi	205.98
	F40B.0	daN	3664	mm	180	daN/cm ²	14.4
		lbf	8237	inch	7.087	psi	208.83
F45A		daN	3841	mm	140	daN/cm ²	25.0
		lbf	8635	inch	5.512	psi	361.89
F50A	F50A.0	daN	4197	mm	180	daN/cm ²	16.5
		lbf	9435	inch	7.087	psi	239.21
F55AXP	F55A.0	daN	4197	mm	180	daN/cm ²	16.5
		lbf	9435	inch	7.087	psi	239.21
F60A		daN	4847	mm	140	daN/cm ²	31.5
		lbf	10896	inch	5.512	psi	456.67

F60AXS		daN	4805	mm	140	daN/cm ²	31.2
		lbf	10802	inch	5.512	psi	452.72
F65A	F65A.0	daN	5055	mm	180	daN/cm ²	19.9
		lbf	11364	inch	7.087	psi	288.12
F65AK	F65AK.0	daN	4994	mm	180	daN/cm ²	19.6
		lbf	11227	inch	7.087	psi	284.64
	F65B.0	daN	5031	mm	180	daN/cm ²	19.8
		lbf	11310	inch	7.087	psi	286.75
	F65B.1	daN	5127	mm	180	daN/cm ²	20.1
		lbf	11526	inch	7.087	psi	292.22
F70		daN	5702	mm	140	daN/cm ²	37.0
		lbf	12819	inch	5.512	psi	537.23
F70AXP	F70A.0	daN	5191	mm	180	daN/cm ²	20.4
		lbf	11670	inch	7.087	psi	295.87
F70AKXP	F70AK.0	daN	5388	mm	180	daN/cm ²	21.2
		lbf	12113	inch	7.087	psi	307.09
	F70B.0	daN	5100	mm	180	daN/cm ²	20.0
		lbf	11465	inch	7.087	psi	290.68
	F70B.1	daN	5186	mm	180	daN/cm ²	20.4
		lbf	11659	inch	7.087	psi	295.58
F80A	F80A.0	daN	6645	mm	180	daN/cm ²	26.1
		lbf	14939	inch	7.087	psi	378.74
F80AXS		daN	6593	mm	140	daN/cm ²	42.8
		lbf	14822	inch	5.512	psi	621.18
F80AK	F80AK.0	daN	6606	mm	180	daN/cm ²	26.0
		lbf	14851	inch	7.087	psi	376.52
	F85B.0	daN	6872	mm	180	daN/cm ²	27.0
		lbf	15449	inch	7.087	psi	391.68
	F85B.1	daN	6327	mm	180	daN/cm ²	24.9
		lbf	14224	inch	7.087	psi	360.61
	F85B.2	daN	6297	mm	180	daN/cm ²	24.7
		lbf	14156	inch	7.087	psi	358.90
F90AXP	F90A.0	daN	6656	mm	180	daN/cm ²	26.2
		lbf	14963	inch	7.087	psi	379.37
F90AKXP	F90AK.0	daN	7002	mm	180	daN/cm ²	27.5
		lbf	15741	inch	7.087	psi	399.09
	F90B.0	daN	6872	mm	180	daN/cm ²	27.0
		lbf	15449	inch	7.087	psi	391.68
	F90B.1	daN	6327	mm	180	daN/cm ²	24.9
		lbf	14224	inch	7.087	psi	360.61
	F90B.2	daN	6297	mm	180	daN/cm ²	24.7
		lbf	14156	inch	7.087	psi	358.90
F95A	F95A.0	daN	6552	mm	180	daN/cm ²	25.7
		lbf	14729	inch	7.087	psi	373.44
F95AXS	F95AXS	daN	6524	mm	180	daN/cm ²	25.6
		lbf	14667	inch	7.087	psi	371.84
F95AK	F95AK.0	daN	6446	mm	180	daN/cm ²	25.3
		lbf	14491	inch	7.087	psi	367.40
	F95B.0	daN	6128	mm	180	daN/cm ²	24.1
		lbf	13776	inch	7.087	psi	349.27

	F100B.1	daN	6327	mm	180	daN/cm ²	24.9
		lbf	14224	inch	7.087	psi	360.61
	F100B.2	daN	6297	mm	180	daN/cm ²	24.7
		lbf	14156	inch	7.087	psi	358.90
F100AT	F100AT	daN	6856	mm	180	daN/cm ²	26.9
		lbf	15413	inch	7.087	psi	390.77
F105AXP	F105A.0	daN	6708	mm	180	daN/cm ²	26.4
		lbf	15080	inch	7.087	psi	382.33
F105AKXP	F105AK.0	daN	6591	mm	180	daN/cm ²	25.9
		lbf	14817	inch	7.087	psi	375.66
	F105B.0	daN	6422	mm	180	daN/cm ²	25.2
		lbf	14437	inch	7.087	psi	366.03
F110A	F110A.0	daN	7256	mm	180	daN/cm ²	28.5
		lbf	16312	inch	7.087	psi	413.56
	F110AT.0	daN	6856	mm	180	daN/cm ²	26.9
		lbf	15413	inch	7.087	psi	390.77
F110AXS	F110AXS	daN	7234	mm	180	daN/cm ²	28.4
		lbf	16263	inch	7.087	psi	412.31
F110AK	F110AK	daN	7239	mm	180	daN/cm ²	28.4
		lbf	16274	inch	7.087	psi	412.59
	F110B.0	daN	6646	mm	180	daN/cm ²	26.1
		lbf	14941	inch	7.087	psi	378.80
	F110B.1	daN	7417	mm	180	daN/cm ²	29.1
		lbf	16674	inch	7.087	psi	422.74
	F110B.2	daN	7509	mm	180	daN/cm ²	29.5
		lbf	16881	inch	7.087	psi	427.98
	F115A.0	daN	7256	mm	180	daN/cm ²	28.5
		lbf	16312	inch	7.087	psi	413.56
	F115AXS	daN	7234	mm	180	daN/cm ²	28.4
		lbf	16263	inch	7.087	psi	412.31
F120AXP	F120A.0	daN	7559	mm	180	daN/cm ²	29.7
		lbf	16993	inch	7.087	psi	430.83
F120AS		daN	7916	mm	140	daN/cm ²	51.4
		lbf	17796	inch	5.512	psi	745.83
F120AKXP	F120AK.0	daN	7239	mm	180	daN/cm ²	28.4
		lbf	16274	inch	7.087	psi	412.59
F120ATXP	F120ATXP	daN	6856	mm	180	daN/cm ²	26.9
		lbf	15413	inch	7.087	psi	390.77
	F120BCM.1	daN	9878	mm	180	daN/cm ²	38.8
		lbf	22207	inch	7.087	psi	563.01
	F120B.0	daN	6874	mm	180	daN/cm ²	27.0
		lbf	15453	inch	7.087	psi	391.79
	F120B.1	daN	7417	mm	180	daN/cm ²	29.1
		lbf	16674	inch	7.087	psi	422.74
	F120B.2	daN	7509	mm	180	daN/cm ²	29.5
		lbf	16881	inch	7.087	psi	427.98
	F125A.1	daN	7417	mm	180	daN/cm ²	29.1
		lbf	16674	inch	7.087	psi	422.74
	F125A.2	daN	7509	mm	180	daN/cm ²	29.5
		lbf	16881	inch	7.087	psi	427.98

	F130A.0	daN	7559	mm	180	daN/cm ²	29.7
		lbf	16993	inch	7.087	psi	430.83
F130A	F135A.0	daN	8490	mm	180	daN/cm ²	33.4
		lbf	19086	inch	7.087	psi	483.90
F130AT	F130AT	daN	7637	mm	180	daN/cm ²	30.0
		lbf	17169	inch	7.087	psi	435.28
	F130AT.0	daN	6856	mm	180	daN/cm ²	26.9
		lbf	15413	inch	7.087	psi	390.77
F130AXS	F135AXS	daN	8434	mm	180	daN/cm ²	33.1
		lbf	18960	inch	7.087	psi	480.70
F130AK	F135AK.0	daN	8430	mm	180	daN/cm ²	33.1
		lbf	18951	inch	7.087	psi	480.48
F135A	F135A.2	daN	8847	mm	180	daN/cm ²	34.8
		lbf	19889	inch	7.087	psi	504.24
	F140AT.0	daN	7637	mm	180	daN/cm ²	30.0
		lbf	17169	inch	7.087	psi	435.28
F145AS	F145AS	daN	7100	mm	180	daN/cm ²	27.9
		lbf	15961	inch	7.087	psi	404.67
	F145AZ	daN	9410	mm	180	daN/cm ²	37.0
		lbf	21155	inch	7.087	psi	536.33
F150A	F155A.0	daN	9358	mm	180	daN/cm ²	36.8
		lbf	21038	inch	7.087	psi	533.37
	F150A.2	daN	8378	mm	180	daN/cm ²	32.9
		lbf	18834	inch	7.087	psi	477.51
F150ATXP	F150ATXP	daN	7637	mm	180	daN/cm ²	30.0
		lbf	17169	inch	7.087	psi	435.28
F150AXS	F155AXS	daN	9336	mm	180	daN/cm ²	36.7
		lbf	20988	inch	7.087	psi	532.12
F150AK	F155AK.0	daN	9177	mm	180	daN/cm ²	36.1
		lbf	20631	inch	7.087	psi	523.05
F155A	F155A.2	daN	9547	mm	180	daN/cm ²	37.5
		lbf	21463	inch	7.087	psi	544.14
	F160A.2	daN	8152	mm	180	daN/cm ²	32.0
		lbf	18326	inch	7.087	psi	464.63
F160AXP	F165A.0	daN	9374	mm	180	daN/cm ²	36.8
		lbf	21074	inch	7.087	psi	534.28
F160ASXP	F160ASXP	daN	7100	mm	180	daN/cm ²	27.9
		lbf	15961	inch	7.087	psi	404.67
	F160AT.0	daN	7637	mm	180	daN/cm ²	30.0
		lbf	17169	inch	7.087	psi	435.28
F160AS		daN	9363	mm	200	daN/cm ²	29.8
		lbf	21049	inch	7.874	psi	432.26
F160AKXP	F165AK.0	daN	9299	mm	180	daN/cm ²	36.5
		lbf	20905	inch	7.087	psi	530.01
F165AXP	F165A.2	daN	9547	mm	180	daN/cm ²	37.5
		lbf	21463	inch	7.087	psi	544.14
	F165AT.0	daN	7637	mm	180	daN/cm ²	30.0
		lbf	17169	inch	7.087	psi	435.28
	F165AZ.0	daN	10553	mm	180	daN/cm ²	41.5
		lbf	23724	inch	7.087	psi	601.48

F170A	F175A.0	daN	9276	mm	180	daN/cm ²	36.5
		lbf	20853	inch	7.087	psi	528.70
F170A	F175ADMO.0	daN	8858	mm	180	daN/cm ²	34.8
		lbf	19914	inch	7.087	psi	504.87
F170AS		daN	8490	mm	200	daN/cm ²	27.0
		lbf	19086	inch	7.874	psi	391.96
F170AT	F170AT	daN	9185	mm	180	daN/cm ²	36.1
		lbf	20649	inch	7.087	psi	523.51
	F175A.1	daN	9921	mm	180	daN/cm ²	39.0
		lbf	22303	inch	7.087	psi	565.46
F175A	F175A.2	daN	9430	mm	180	daN/cm ²	37.1
		lbf	21199	inch	7.087	psi	537.47
	F180AT.0	daN	9185	mm	180	daN/cm ²	36.1
		lbf	20649	inch	7.087	psi	523.51
F185AS	F185AS	daN	8394	mm	200	daN/cm ²	26.7
		lbf	18870	inch	7.874	psi	387.52
	F185A.1	daN	9921	mm	180	daN/cm ²	39.0
		lbf	22303	inch	7.087	psi	565.46
	F185A.2	daN	9571	mm	180	daN/cm ²	37.6
		lbf	21516	inch	7.087	psi	545.51
F185BS	F185BS	daN	8394	mm	250	daN/cm ²	17.1
		lbf	18870	inch	9.843	psi	248.02
F190A	F195A.0	daN	9947	mm	250	daN/cm ²	20.3
		lbf	22362	inch	9.843	psi	293.90
F190ATXP	F190ATXP	daN	9185	mm	180	daN/cm ²	36.1
		lbf	20649	inch	7.087	psi	523.51
	F195A.1	daN	9955	mm	180	daN/cm ²	39.1
		lbf	22380	inch	7.087	psi	567.40
F195A	F195A.2	daN	10180	mm	250	daN/cm ²	20.7
		lbf	22886	inch	9.843	psi	300.79
	F195AS	daN	9550	mm	250	daN/cm ²	19.5
		lbf	21469	inch	9.843	psi	282.17
	F200AT.0	daN	9185	mm	180	daN/cm ²	36.1
		lbf	20649	inch	7.087	psi	523.51
	F205AT.0	daN	9185	mm	180	daN/cm ²	36.1
		lbf	20649	inch	7.087	psi	523.51
F200ASXP	F210ASXP	daN	8394	mm	200	daN/cm ²	26.7
		lbf	18870	inch	7.874	psi	387.52
	F210ASXP	daN	9965	mm	250	daN/cm ²	20.3
		lbf	22402	inch	9.843	psi	294.43
F200BSXP	F210BSXP	daN	8394	mm	250	daN/cm ²	17.1
		lbf	18870	inch	9.843	psi	248.02
F210A	F215A.0	daN	10646	mm	250	daN/cm ²	21.7
		lbf	23933	inch	9.843	psi	314.55
	F215ALP.0	daN	9349	mm	250	daN/cm ²	19.0
		lbf	21017	inch	9.843	psi	276.23
F215A	F215A.2	daN	10935	mm	250	daN/cm ²	22.3
		lbf	24583	inch	9.843	psi	323.09
F215AS	F215AS	daN	11093	mm	250	daN/cm ²	22.6
		lbf	24938	inch	9.843	psi	327.76

Outrigger Ground Pressures (Feb 2024)

	F215AZ.1	daN	10119	mm	250	daN/cm ²	20.6
		lbf	22748	inch	9.843	psi	298.98
	F215RA.2	daN	10131	mm	250	daN/cm ²	20.6
		lbf	22775	inch	9.843	psi	299.34
F220A		daN	12280	mm	200	daN/cm ²	39.1
		lbf	27607	inch	7.874	psi	566.93
F230AXP	F235A.0	daN	10755	mm	250	daN/cm ²	21.9
		lbf	24178	inch	9.843	psi	317.78
F230SE		daN	14124	mm	200	daN/cm ²	45.0
		lbf	31752	inch	7.874	psi	652.06
F235AXP	F235A.2	daN	10935	mm	250	daN/cm ²	22.3
		lbf	24583	inch	9.843	psi	323.09
	F235RA.2	daN	10131	mm	250	daN/cm ²	20.6
		lbf	22775	inch	9.843	psi	299.34
F240A		daN	12974	mm	200	daN/cm ²	41.3
		lbf	29167	inch	7.874	psi	598.97
F240ASXP	F240ASXP	daN	11093	mm	250	daN/cm ²	22.6
		lbf	24938	inch	9.843	psi	327.76
F240B		daN	13055	mm	200	daN/cm ²	41.6
		lbf	29349	inch	7.874	psi	602.71
F240D	F245A.0	daN	13000	mm	250	daN/cm ²	26.5
		lbf	29225	inch	9.843	psi	384.11
F245A	F245A.2	daN	13055	mm	250	daN/cm ²	26.6
		lbf	29349	inch	9.843	psi	385.73
	F245AZ.1	daN	11411	mm	250	daN/cm ²	23.2
		lbf	25653	inch	9.843	psi	337.16
F250A		daN	13807	mm	200	daN/cm ²	43.9
		lbf	31039	inch	7.874	psi	637.43
F250SE		daN	14738	mm	500	daN/cm ²	7.5
		lbf	33132	inch	19.685	psi	108.87
	F255A.2	daN	10935	mm	250	daN/cm ²	22.3
		lbf	24583	inch	9.843	psi	323.09
	F255RA.2	daN	10365	mm	250	daN/cm ²	21.1
		lbf	23301	inch	9.843	psi	306.25
F260AXP		daN	12628	mm	200	daN/cm ²	40.2
		lbf	28389	inch	7.874	psi	582.99
F260BXP		daN	12795	mm	200	daN/cm ²	40.7
		lbf	28764	inch	7.874	psi	590.70
F260DXP	F275A.0	daN	13000	mm	250	daN/cm ²	26.5
		lbf	29225	inch	9.843	psi	384.11
F270A		daN	14425	mm	200	daN/cm ²	45.9
		lbf	32429	inch	7.874	psi	665.96
F270AXP	F275A.2	daN	13055	mm	250	daN/cm ²	26.6
		lbf	29349	inch	9.843	psi	385.73
	F275RA.2	daN	12598	mm	250	daN/cm ²	25.7
		lbf	28321	inch	9.843	psi	372.23
F280SE	F280SE	daN	15023	mm	500	daN/cm ²	7.7
		lbf	33773	inch	19.685	psi	110.97
F290A	F295A.2	daN	15832	mm	250	daN/cm ²	32.3
		lbf	35592	inch	9.843	psi	467.78

F295A	F295RA.2	daN	15407	mm	250	daN/cm ²	31.4
		lbf	34636	inch	9.843	psi	455.23
F300AXP		daN	14378	mm	200	daN/cm ²	45.8
		lbf	32323	inch	7.874	psi	663.79
F300SE		daN	13365	mm	500	daN/cm ²	6.8
		lbf	30046	inch	19.685	psi	98.72
	F305A.2	daN	13055	mm	250	daN/cm ²	26.6
		lbf	29349	inch	9.843	psi	385.73
	F305RA.2	daN	12975	mm	250	daN/cm ²	26.4
		lbf	29169	inch	9.843	psi	383.37
F310AXP	F315A.2	daN	15832	mm	250	daN/cm ²	32.3
		lbf	35592	inch	9.843	psi	467.78
	F315B.2	daN	14928	mm	250	daN/cm ²	30.4
		lbf	33559	inch	9.843	psi	441.07
F315AXP	F315RA.2	daN	15407	mm	250	daN/cm ²	31.4
		lbf	34636	inch	9.843	psi	455.23
	F315RB.2	daN	14905	mm	250	daN/cm ²	30.4
		lbf	33508	inch	9.843	psi	440.39
F330A		daN	15255	mm	210	daN/cm ²	44.0
		lbf	34295	inch	8.268	psi	638.80
F330SE	F330SE	daN	13450	mm	500	daN/cm ²	6.9
		lbf	30237	inch	19.685	psi	99.35
F330B		daN	15124	mm	210	daN/cm ²	43.7
		lbf	34000	inch	8.268	psi	633.31
F330D	F335A.2	daN	14068	mm	250	daN/cm ²	28.7
		lbf	31626	inch	9.843	psi	415.66
F335A	F335RA.2	daN	13805	mm	250	daN/cm ²	28.1
		lbf	31035	inch	9.843	psi	407.89
	F345A.2	daN	15832	mm	250	daN/cm ²	32.3
		lbf	35592	inch	9.843	psi	467.78
	F345B.2	daN	15450	mm	250	daN/cm ²	31.5
		lbf	34733	inch	9.843	psi	456.50
	F345RA.2	daN	15407	mm	250	daN/cm ²	31.4
		lbf	34636	inch	9.843	psi	455.23
	F345RB.2	daN	15393	mm	250	daN/cm ²	31.4
		lbf	34605	inch	9.843	psi	454.81
F360AXP		daN	15273	mm	210	daN/cm ²	44.1
		lbf	34335	inch	8.268	psi	639.55
F360BXP		daN	15306	mm	210	daN/cm ²	44.2
		lbf	34409	inch	8.268	psi	640.93
	F360SE	daN	12286	mm	500	daN/cm ²	6.3
		lbf	27620	inch	19.685	psi	90.75
F360DXP	F365A.2	daN	14415	mm	250	daN/cm ²	29.4
		lbf	32406	inch	9.843	psi	425.92
F365AXP	F365RA.2	daN	13925	mm	250	daN/cm ²	28.4
		lbf	31305	inch	9.843	psi	411.44
	F375SE	daN	11702	mm	500	daN/cm ²	6.0
		lbf	26307	inch	19.685	psi	86.44

F380A		daN	16966	mm	210	daN/cm ²	49.0
		lbf	38141	inch	8.268	psi	710.45
F380B	F385A.2	daN	16298	mm	250	daN/cm ²	33.2
		lbf	36639	inch	9.843	psi	481.55
F380SE		daN	17624	mm	500	daN/cm ²	9.0
		lbf	39620	inch	19.685	psi	130.18
F385A	F385RA.2	daN	17863	mm	250	daN/cm ²	36.4
		lbf	40158	inch	9.843	psi	527.79
F390SE	F390SE	daN	18493	mm	500	daN/cm ²	9.4
		lbf	41574	inch	19.685	psi	136.60
	F395A.2	daN	14420	mm	250	daN/cm ²	29.4
		lbf	32417	inch	9.843	psi	426.06
	F395RA.2	daN	14442	mm	250	daN/cm ²	29.4
		lbf	32467	inch	9.843	psi	426.71
	F400E.2	daN	14420	mm	250	daN/cm ²	29.4
		lbf	32417	inch	9.843	psi	426.06
F410A		daN	18471	mm	210	daN/cm ²	53.3
		lbf	41524	inch	8.268	psi	773.47
F410B	F415A.2	daN	17546	mm	250	daN/cm ²	35.7
		lbf	39445	inch	9.843	psi	518.43
F415A	F415RA.2	daN	19235	mm	250	daN/cm ²	39.2
		lbf	43242	inch	9.843	psi	568.33
F420AXP		daN	17147	mm	210	daN/cm ²	49.5
		lbf	38548	inch	8.268	psi	718.02
F420BXP	F425A.2	daN	16716	mm	250	daN/cm ²	34.1
		lbf	37579	inch	9.843	psi	493.90
F425AXP	F425RA.2	daN	18331	mm	250	daN/cm ²	37.3
		lbf	41210	inch	9.843	psi	541.62
	F425SE.04	daN	12679	mm	500	daN/cm ²	6.5
		lbf	28504	inch	19.685	psi	93.66
F450AXP		daN	18290	mm	210	daN/cm ²	52.8
		lbf	41118	inch	8.268	psi	765.89
F450BXP	F455A.2	daN	17933	mm	250	daN/cm ²	36.5
		lbf	40315	inch	9.843	psi	529.86
	F485A.2	daN	18211	mm	250	daN/cm ²	37.1
		lbf	40940	inch	9.843	psi	538.08
F455AXP	F455RA.2	daN	19652	mm	250	daN/cm ²	40.0
		lbf	44179	inch	9.843	psi	580.65
	F485RA.2	daN	19951	mm	250	daN/cm ²	40.6
		lbf	44852	inch	9.843	psi	589.49
F460		daN	19202	mm	210	daN/cm ²	55.4
		lbf	43168	inch	8.268	psi	804.08
F480A		daN	20047	mm	210	daN/cm ²	57.9
		lbf	45067	inch	8.268	psi	839.46
F510A	F510RA.2	daN	18224	mm	400	daN/cm ²	14.5
		lbf	40969	inch	15.748	psi	210.34
	F515RA.2	daN	15811	mm	250	daN/cm ²	32.2
		lbf	35545	inch	9.843	psi	467.16
F520XP		daN	19386	mm	210	daN/cm ²	56.0
		lbf	43581	inch	8.268	psi	811.78

F530AXP		daN	19850	mm	210	daN/cm ²	57.3
		lbf	44625	inch	8.268	psi	831.21
F540A		daN	21757	mm	210	daN/cm ²	62.8
		lbf	48912	inch	8.268	psi	911.07
F545RA.2	F545RA.2	daN	16097	mm	250	daN/cm ²	32.8
		lbf	36187	inch	9.843	psi	475.61
F560AXP	F560RA.2	daN	18732	mm	400	daN/cm ²	14.9
		lbf	42111	inch	15.748	psi	216.20
F600AXP		daN	21806	mm	210	daN/cm ²	63.0
		lbf	49022	inch	8.268	psi	913.12
F600A	F600RA.2	daN	20146	mm	400	daN/cm ²	16.0
		lbf	45290	inch	15.748	psi	232.52
F600SE.44	F600SE.44	daN	21970	mm	500	daN/cm ²	11.2
		lbf	49391	inch	19.685	psi	162.29
F660AXP	F660RA.2	daN	20146	mm	400	daN/cm ²	16.0
		lbf	45290	inch	15.748	psi	232.52
F700XP		daN	23944	mm	210	daN/cm ²	69.1
		lbf	53828	inch	8.268	psi	1002.65
F800		daN	27190	mm	210	daN/cm ²	78.5
		lbf	61126	inch	8.268	psi	1138.57
F700A		daN	24177	mm	400	daN/cm ²	19.2
		lbf	54352	inch	15.748	psi	279.04
F700B	F700RA.2	daN	24177	mm	400	daN/cm ²	19.2
		lbf	54352	inch	15.748	psi	279.04
F710RA.2	F710RA.2	daN	20146	mm	400	daN/cm ²	16.0
		lbf	45290	inch	15.748	psi	232.52
F720RA.2	F720RA.2	daN	24177	mm	400	daN/cm ²	19.2
		lbf	54352	inch	15.748	psi	279.04
F800AXP		daN	24584	mm	400	daN/cm ²	19.6
		lbf	55267	inch	15.748	psi	283.74
F800BXP	F800RA.2	daN	24584	mm	400	daN/cm ²	19.6
		lbf	55267	inch	15.748	psi	283.74
F820RA.3	F820RA.3	daN	24984	mm	400	daN/cm ²	19.9
		lbf	56166	inch	15.748	psi	288.36
F850A		daN	25572	mm	400	daN/cm ²	20.3
		lbf	57488	inch	15.748	psi	295.14
F900XP		daN	27465	mm	210	daN/cm ²	79.3
		lbf	61744	inch	8.268	psi	1150.09
F900A		daN	27610	mm	210	daN/cm ²	79.7
		lbf	62070	inch	8.268	psi	1156.16
F950AXP	F950RA.2	daN	26261	mm	400	daN/cm ²	20.9
		lbf	59037	inch	15.748	psi	303.10
F990RA.2	F990RA.2	daN	26402	mm	400	daN/cm ²	21.0
		lbf	59354	inch	15.748	psi	304.72
F1000AXP		daN	28170	mm	210	daN/cm ²	81.3
		lbf	63329	inch	8.268	psi	1179.61
F1000A		daN	27327	mm	400	daN/cm ²	21.7
		lbf	61434	inch	15.748	psi	315.40
F1100AXP	F1100RA.2	daN	28915	mm	400	daN/cm ²	23.0
		lbf	65003	inch	15.748	psi	333.73

	F1150RA.2	daN	28636	mm	400	daN/cm ²	22.8
		lbf	64376	inch	15.748	psi	330.51
	F1250R.2-HXP	daN	28792	mm	400	daN/cm ²	22.9
		lbf	64727	inch	15.748	psi	332.31
F1200A		daN	28331	mm	500	daN/cm ²	14.4
		lbf	63691	inch	19.685	psi	209.27
F1300AXP	F1300RA.2	daN	29830	mm	500	daN/cm ²	15.2
		lbf	67060	inch	19.685	psi	220.35
	F1350RA.2	daN	30054	mm	500	daN/cm ²	15.3
		lbf	67564	inch	19.685	psi	222.00
F1400A		daN	35657	mm	500	daN/cm ²	18.2
		lbf	80160	inch	19.685	psi	263.39
	F1450R.2-HXP	daN	32907	mm	500	daN/cm ²	16.8
		lbf	73978	inch	19.685	psi	243.07
F1500AXP	F1500RA.2	daN	36584	mm	500	daN/cm ²	18.6
		lbf	82244	inch	19.685	psi	270.23
	F1550RA.2	daN	36584	mm	500	daN/cm ²	18.6
		lbf	82244	inch	19.685	psi	270.23
	F1600RA.2	daN	35867	mm	500	daN/cm ²	18.3
		lbf	80632	inch	19.685	psi	264.94
	F1600RAL.2	daN	33886	mm	500	daN/cm ²	17.3
		lbf	76179	inch	19.685	psi	250.31
	F1650RA.2	daN	36664	mm	500	daN/cm ²	18.7
		lbf	82424	inch	19.685	psi	270.83
	F1650RAL.2	daN	35595	mm	500	daN/cm ²	18.1
		lbf	80021	inch	19.685	psi	262.93
	F1750R.2-HXP	daN	37270	mm	500	daN/cm ²	19.0
		lbf	83786	inch	19.685	psi	275.30
	F1750RL.2-HXP	daN	36326	mm	500	daN/cm ²	18.5
		lbf	81664	inch	19.685	psi	268.33
	F1950RA.2	daN	36991	mm	500	daN/cm ²	18.8
		lbf	83159	inch	19.685	psi	273.24
	F1950RAL.2	daN	37294	mm	500	daN/cm ²	19.0
		lbf	83840	inch	19.685	psi	275.48
	F2150RA.2	daN	43064	mm	500	daN/cm ²	21.9
		lbf	96812	inch	19.685	psi	318.10
	F2150RAL.2	daN	39261	mm	500	daN/cm ²	20.0
		lbf	88262	inch	19.685	psi	290.01
	F2350RL.2-HXP	daN	40308	mm	500	daN/cm ²	20.5
		lbf	90616	inch	19.685	psi	297.74